

Technical data sheet

Wireless accessories

A fully integrated system

The TV Adapter connects directly to the user's hearing aids, allowing for hassle-free daily use.

Ease of use

The TV Adapter has been developed and thoroughly tested with hearing aid users in mind to ensure optimal ease of use.

Dolby Digital® and Digital Stereo

The TV Adapter supports digital sound in two widely used formats: Digital Stereo (PCM) and Dolby Digital®. This increases the opportunities for users to benefit from streamed sound from home theater systems and flat panel TVs.

MultiConnect

The TV Adapter can be connected to an unlimited number of hearing aids at the same time, allowing for several users to share the same experience.

Easy pairing

Once hearing aids are in pairing mode and within 30 cm of the TV Adapter, the TV Adapter will automatically pair and connect to them.

More information

Please visit www.oticon.com for more information about the TV Adapter.

TV Adapter 3.0



TV Adapter 3.0 enables Oticon hearing aid users to enjoy the stereo sound from a TV, home entertainment system, radio or other audio source at their preferred sound level streamed directly to their hearing aids. TV Adapter 3.0 supports a range of connections, including Digital Stereo and Dolby Digital® through optical TOSLINK.





Power indicator TV indicator



Power RCA L+R TOSLINK In and Out

Included

- Instructions for use
- Power supply
- TV Adapter - black
- TOSLINK optical cable 6.5 feet (2 m)
- SCART to RCA converter
- RCA to RCA stereo cable
- Minijack 3.5mm to RCA converter

Technical data	
Model	TVA3
Operating conditions	Temperature: +5°C to +40°C Humidity: 15% to 93%, non-condensing
Storage and transportation conditions	Temperature: -25 °C to +70 °C Humidity: 15% to 93%, non-condensing
Dimensions	124 x 80 x 21 mm; weight 107 g.
System features	Autopairing: TV Adapter will automatically pair with hearing aids in pairing mode AutoStream: TV Adapter will automatically start streaming audio when a valid audio signal is detected MultiConnect: TV Adapter can connect to an unlimited number of hearing aids
Compatibility	The TV Adapter works with all versions of Oticon hearing aids with 2.4GHz radio technology
Input connectors/format	Minijack 3.5 mm (L+R) (using included cable and converter) SCART (L+R) using included converter and RCA cable RCA (L+R) TOSLINK Digital Stereo (PCM)/Dolby Digital®
Output	TOSLINK (buffered output of TOSLINK input)
Range	Up to 50 feet (15 m) (free line of sight from TV Adapter to hearing aids)
Audio inputs (format)	Stereo analog input (RCA) Stereo/PCM (TOSLINK) Dolby digital® (TOSLINK)
Latency (TV Adapter input to hearing aid speaker)	Analog: 25 ms Digital: 28 ms Dolby Digital®: 45 ms
Line input sensitivity	6 dB Vrms (analog), impedance: 10 KΩ
Audio bandwidth	10 KHz/stereo from input to hearing aids
Dynamic self-adjustment	AGC (analog inputs) (line in approximation to 0 dB 5 secs)
Status indicators	Power and status LED on front
Colors	Black
Frequency	License free 2.4 GHz (ISM band)
Emissions	Max 17.1 dBm EIRP. In compliance with all relevant standards
Power consumption	Idle, not streaming sound: 0.8 W Streaming sound: 1.5 W